

HOT OIL/热油

ISO 340/284

Hot oil / fire resistant
ISO 340/284

热油/阻燃性 ISO 340/284



www.go4b.com

Suitable for use in ATEX applications.

This special belt offers resistance to the combination of fats and oils and higher processing temperature up to 120°C in often humid working environments.

The belt is specially aimed at solving high temperature problems in processing of soya beans, cattle feed, rape seed and fat processing.

适合在 ATEX 应用环境中使用。

这种特殊的输送带可以在通常潮湿的工作环境中承受油脂以及 120°C 以下的较高处理温度的共同侵蚀。

这种输送带专用于解决在加工黄豆、牲畜饲料、油菜籽以及油脂加工的过程中出现的高温问题。



HOT OIL AND FIRE RESISTANT BELT

热油与阻燃输送带



Temperature Range -20°C to +120°C /
温度范围为 -20°C 至 +120°C



Belt
输送带

Thickness
厚度
(mm)

Weight
重量
(kg/m²)

Minimum Pulley Ø
最小皮带轮Ø
(mm)

EP800/4 2+2 NBR T120

9.0

9.8

500

Hot oil / fire resistant
ISO 340/284

Technical Specifications

- Product Norm: DIN 22102 ETGX
- E = anti-static DIN 22104
- T = heat resistant to 120°C for fatty products
- G = both covers and textile plies resistant to mineral, animal and vegetables oils and fats, low concentrations of acids, lyes and water resistant
- X = good abrasion resistance
- K = flame retardant DIN 22103K - ISO 340/EN 20340
- Elongation at maximum recommendation working load - 1.5-2.0%

热油/阻燃性 ISO 340/284

技术规格

- 产品规范: DIN 22102 ETGX
- E = 防静电 DIN 22104
- T = 对于含脂肪的产品, 耐 120°C 以下的高温
- G = 封盖和织物层均对矿物、动物及植物油脂, 以及低浓度的酸、碱液和水具有耐性
- X = 良好的耐磨性
- K = 阻燃性 DIN 22103K - ISO 340/EN 20340
- 在最大建议工作负载下, 延伸率为 1.5-2.0%

