TYPE SJ STARCO JUMBO™

Developed to meet the needs of industrial elevators, particularly cement. Deep drawn solid steel bucket, designed and engineered to replace large fabricated buckets. Suitable for use with both standard rubber and steel cord belting.

- > Improved capacity: Wingless design, improves fill and allows closer spacing
- > Greater strength/longer life: Solid seamless construction with rounded corners for rigidity. No welds or joints to open up
- > Economic solution
- > More buckets per metre: More capacity, smaller casing

Industrial PRESSED SEAMLESS STEEL В G **Z**3 øΕ Capacity (Litres) **Recessed Holes** G (mm) Max. Pcs/Mtr B (mm) T (mm) Z2 (total) Z3 (water) E (Ø mm) F (mm) (kg) No. SJ330-250/3 340 260 190 130 3.0 4.5 9.6 7.2 13 80 55 5 SJ330-250/4 340 260 190 130 4.0 6.0 9.6 7.2 3 13 80 55 5 SJ370-250/3 380 260 190 130 3.0 5.1 10.8 8.3 4 13 80 55 5 SJ370-250/4 380 260 190 130 6.8 10.8 8.3 13 80 55 4.0 4 5 SJ470-250/3 480 260 190 130 3.0 6.5 14.0 10.5 5 13 80 55 5 SJ470-250/4 480 260 190 130 4.0 8.6 14.0 10.5 5 13 80 55 5 Special holes/thicknesses/wearbands - available on request

Free Engineering Design Service - contact 4B or visit: www.go4b.com

